

Big bags 1000 kg



Bags 25 kg



Pellet length 7 - 12 mm



Swelling capacity 180 - 200%

TECHNICAL DATA



 T n the Mikolit $^\circ$ product-range, Mikolit $^\circ$ B is the top product. Mikolit $^\circ$ B is manufactured from a mix of $oldsymbol{\perp}$ activated calcium bentonites, with a very high swelling capacity. After the spaces between the grains have been filled up, only a small part of the swelling capacity has been consumed. The introduced clay will built a relatively dry, fixed clay layer. The quality B has excellent sinking quality's, duet o the fact that the product is free of dust, it has a strongly slowed down start of swelling and it has favourable grain dimensions. The production method, leads to the fact that, in spite of a high swelling capacity the quality B has a strongly slowed down start of swelling. Of course Mikolit® B has a wide degree of self-healing. Also at applications in salty water a good sealing is insured. When applicated in a drilling with temporary casing there is a higher risk that the clay pellets will adhese to the casing.

Product name:	Mikolit® B Green / grey Ø ± 8 mm, length 7 – 12 mm Zakken 25 kg / big bags 1000 kg 21 m/min 1,7 – 1,8 t/m³ 1,0 t/m³ 12 min 180 – 200% ¹)				
Pellet color:					
Pellet size:					
Package:					
Sinking speed in water:					
Density water saturated:					
Bulk density:					
Start of swelling:					
Swelling capacity:					
Permeability:	< 10 ⁻¹² m/s				
Swelling pressure:	12 – 15 kN/m²				
γ-ray:	55 – 85 API				

¹⁾ Free swelling in goblet glass in dem. water, additional to pore volume.

Quantity needed (kg/m)

								Bore-hole (mm) >				
	В	100	125	150	200	250	300	400	500	600		
	0	8	12	18	31	49	70	125	195	280		
	50	6	10	16	29	47	68	123	193	279		
	100		4	10	23	41	62	117	187	273		
	125			5	19	37	58	113	183	269		
(IIIII)	160				11	29	50	105	175	261		
	200					18	39	94	164	250		
	250						21	76	146	232		
	315							47	118	203		
2	400								70	156		
,	500									86		

Distributed by:

Mikolit®-products are produced by:



Engelenkampstraat 71 • Postbus 78 • NL-6130 AM Sittard Telefoon: +31 (0) 46 4 526 662 Fax: +31 (0) 46 4 513 055

E-mail: info@terratech.nl